

Order description
PD-C360/8 Slave white

Order number
EP10055379

EAN code
4015120055379



Short description:

- "Slave" presence detector for extending the field of detection of a "master" presence detector with 360° field of detection for ceiling mounting
- With a **range of up to 8 m** in diameter as a cost-efficient system upgrade with up to 9 further extensions
- LED switch-off possible via DIP switches
- Masking of interference sources by reducing sensitivity using DIP switches
- Recessed-mounted device as standard
- Surface mounting or recessed ceiling mounting with accessories
- Easily replaceable/paintable cover and design ring (available in "silver" as an accessory)
- Targeted masking out of areas by means of enclosed lens mask
- "Slave" detector can be connected to the following presence detectors: PD-C360i/8, PD-C360i/8plus, PD-C360i/24plus, PD-C360i/8 DIMplus, PD-C360i/24 DIMplus, PD-C360i/24 DUOplus, PD-C360i/24 Dry, PD-C360i/8 Dali, PD-C360i/24 Dali

Technical data:

Mains voltage	230 V AC, 50 - 60 Hz
Approx. power consumption	0.33 W
Viewing distance	360°
Range	approx. 8 m diameter, at an installation height of 3 m
Permissible ambient temperature	0 °C...+50 °C
Protection type	recessed-mounted IP 20, IP 20/IP 54 with surface-mounted box (order separately), recessed ceiling-mounted IP 20 (installation set order separately)
Protection class	II
Included in delivery	Lens mask
Test symbol	TÜV Süd
Installation type	ceiling mounting
Housing material	UV stabilised polycarbonate
Approx. measurements	height 38 mm, Ø 108 mm
Colour	white, similar to RAL 9010

Accessories

- EP10425370 - Surface-mounted box-C IP 20 white
- EP10425387 - Surface-mounted box-C IP 20 silver
- EP10425905 - Surface-mounted box-C IP 54 white
- EP10425912 - Surface-mounted box-C IP 54 silver
- EP10425929 - Ceiling-mounted set-C white
- EP10425936 - Cover set-C360/8 silver

Order description
PD-C360/8 Slave white

Order number
EP10055379

EAN code
4015120055379

