

LUXOMAT® PD2-M-1C-SM/-FC/-FM




SM




FC




FM



SM



FC




FM

TECHNICAL DATA

- 230V~ ±10%
- 360°
- seated Ø 4.00 m
- across Ø 10.00 m
- towards Ø 6.00 m
- SM/FC/FM = IP20 / Class II / CEE
- SM** Ø 98 x H 50 mm
- FC** Ø 80 x H 84.5 mm
- FM** Ø 98 x H 65 mm
- 25°C to +50°C
- Housing UV- and shock-resistant Polycarbonate
- IR-PD, IR-PD-Mini
- Channel 1 (Control the lighting)**
- 2300 W, cosφ = 1; 1150 VA, cosφ = 0.5
- 15 sec. - 30 min. or impulse
- 10 - 2000 Lux

PRODUCT INFORMATION

- Remote controllable occupancy detector for inside use LUXOMAT® PD2-M-1C as Master version for surface, false ceiling and flush mounting with circular detection area
- One channel to switch the lighting (potential free)
- Switching for all types of light fixtures by high performance relay
- Optical system, designed for highest sensitivity
- The connection of a unlimited number of slaves for reasonable extension is possible!
- Serial impulse function
- **Typical applications:** offices, conference rooms, schools, nursery schools, hospitals etc.



- 1 ■ Walking towards
- 2 ■ Walking across
- 3 ■ Seated activity

ACCESSORY (OPTIONAL)

IR-PD




(to order separately)

IR-PD-Mini



(to order separately)

Wire basket



Socket IP54



Blinds



Slaves



PD2-S

Description	Colour	Part number
PD2-M-1C-SM	white	92550
PD2-M-1C-FC	white	92565
PD2-M-1C-FM	white	92555
Accessory (optional)		
Wire basket BSK	white	92199
LUXOMAT® IR-PD	grey	92160
LUXOMAT® IR-PD-Mini	grey	92159
Socket IP54	white	92161

