




LUXOMAT® PD3-2C-FC/-FM



FC



FM




■ TECHNICAL DATA

- 230V~ ±10%
- 360°
- across Ø 10.00 m
towards Ø 6.00 m
- FC/FM = IP20 / Class II / CE
- FC** Ø 80 x H84.5mm
FM Ø 98 x H65 mm
- 25°C to +50°C
- Housing UV- and shock-resistant Polycarbonate
- Channel 1 (Control the lighting)**
- 2000 W, cosφ = 1;
1000 VA, cosφ = 0.5
- 30sec. - 30 min. or impulse
- 10 - 2000 Lux
- Channel 2 (Control devices)**
- dry contact type NO,
3A, 230 V, cosφ = 1
- 5 - 120 min.

❗ PRODUCT INFORMATION


- Manually operated ceiling-mounted motion detectors LUXOMAT® PD3-2C in ceiling-mount and flush-mount version with circular detection area
- Two switching channels, one to switch the lighting, the second to switch other loads e.g. HVAC by potential free relay of the detector
- Switching for all types of light fixtures by high performance relay
- Optical system, designed for highest sensitivity
- Serial impulse function (gong)
- **Typical applications:** monitoring of smaller areas like stairwells, private garages, galleries, wash rooms



- 1 ■ Walking towards
- 2 ■ Walking across
- 3 ■ Smaller movements

■ ACCESSORY (OPTIONAL)

Wire basket



Covering IP23



Blinds



Description	Colour	Part number
PD3-2C-FC	white	92198
PD3-2C-FM	white	92188
Accessory (optional)		
Wire basket BSK	white	92199
Covering IP23	transparent	92206