

MDT Temperature Controller 6-fold, MDRC
MDT Temperature Controller/Sensor 6-fold, surface mounted
MDT Temperature Controller/Sensor 2-fold, flush mounted

Version		
SCN-RT6REG.01	Temperature Controller 6-fold	2SU MDRC
SCN-RT6AP.01	Controller/Sensor 6-fold	Surface mounted, for PT1000 sensors up to 12m cable length
SCN-RT2UP.01	Controller/Sensor 2-fold	flush mounted, for PT1000 sensors up to 12m cable length
SCN-RT4UP.01	Controller/Sensor 4-fold	flush mounted, for PT1000 sensors up to 12m cable length
Accessories SCN-RT6AP.001		
SCN-PTST1.01	PT 1000 Sensor Standard	Dimensions 4mm x 30mm, 1m cable
SCN-PTST3.01	PT 1000 Sensor Standard	Dimensions 6mm x 50mm, 3m cable
SCN-PTAN3.01	PT 1000 Sensor strap on installation	Dimensions 8mm x 40mm, 3m cable
SCN-PTDE0.01	PT 1000 Sensor ceiling installation	Cut out diameter: 23mm, Depth: 28mm

The MDT Temperature Controller is used for all purpose temperature control applications. The temperature is received as an KNX object or directly from the connected PT1000 temperature sensors (Only SCN-RT6AP.01, SCN-RT2UP.01 or SCN-RT4UP.01). Depending on the adjusted parameters of the Temperature controller the actuating value is sent as 1Bit or 1Byte variable to the bus.

The characteristic of the MDT Temperature Controller (Two-position, PI and PWM control) can be set in the ETS. The thermostat stores the minimum and maximum temperature and releases an alarm telegram if the temperature differs from the programmed limit values.

The temperature of the frost protection is parameterizable. The desired value can be given by MDT VisuControl touchpanel or the MDT pushbuttons.

The MDT Temperature Controller Actuator REG is a modular installation device for fixed installation in dry rooms. It fits on DIN 35mm rails in power distribution boards or closed compact boxes. The Temperature Controller Actuator AP is a surface mounted device, the maximum length of the PT1000 temperature sensors should not exceed 12m.

Both MDT Temperature Controllers are for fixed installations in dry rooms. For project design and commissioning of the MDT Temperature Controllers it is recommended to use the ETS or later. Please download the application software at www.mdt.de/Downloads.html


SCN-RT6REG.01



SCN-RT6AP.01



SCN-RT2UP.01



SCN-PTST3.01



- Production in Germany, certified according to ISO 9001
- Selectable temperature controller (PI, Two-position, PWM)
- Limit values min/max
- Frost-/heat protection alarm,
- Min/max memory
- Cyclical sending of contact state programmable
- Day-/night-/frost-/heat protection operation
- Cooling function
- Status feedback by HVAC and RHCC status objects
- Operation mode can be set via Bit/Byte objects
- Setpoint value via visualisation, e.g. MDT VisuControl
- Integrated bus coupling unit
- 3 years warranty

Technical Data	SCN-RT6REG.01	SCN-RT6AP.01	SCN-RT2UP.01	SCN-RT4UP.01
Number of channels	6	6	2	4
Temperature sensors	--	Connection for PT1000	Connection for PT1000	Connection for PT1000
Max. cable length temperature sensors*	--	12m	12m	12m
Specification KNX Interface	TP-256	TP-256	TP-256	TP-256
Available application software	ETS 3/4/5	ETS 3/4/5	ETS 3/4/5	ETS 3/4/5
Permitted wire gauge				
KNX busconnection terminal	0,8mm Ø, solid core	0,8mm Ø, solid core	0,8mm Ø, solid core	0,8mm Ø, solid core
Power supply**	KNX bus	KNX bus	KNX bus	KNX bus
Power consumption KNX bus typ.	< 0,3W	< 0,3W	< 0,3W	< 0,3W
Operation temperature range	--	-20 bis +100°C	-20 bis +100°C	-20 bis +100°C
Enclosure	IP 20	IP 20	IP 20	IP 20
Dimensions MDRC (Space Units)	2SU	--	--	--
Dimensions (W x H x D)	--	115mm x 64mm x 40mm	41mm x 41mm x 12mm	41mm x 41mm x 12mm

* To avoid radiation, do not install the sensor cables parallel to 230VAC main cables.

** If any 230V cables are in the vicinity, make sure to maintain the distances to them specified as in the applicable standards and regulations. Never install the device in a flush mounted box together with 230V cables.

Exemplary circuit diagramm SCN-RT6REG.01

